Refine Search

Search Results -

Terms	Documents
L19 and L1	1

Database:

```
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins
```

Search:

```
L21
```

[Refine Search]

[Recall Text] [Clear] [Interrupt]

Search History

DATE: Tuesday, May 03, 2005   Printable Copy   Create Case

DB=USPT; PLUR=YES; OP=ADJ

Set Name side by side	Query	Hit Count	Set Name result set
L21	L19 and l1	1	L21
L20	L19 and l17	1	L20
L19	717/126,116,100,108,127,139,140.130,131.ccls.	1237	L19
L18	L17 and ((two$ or mult$ or plural$) near4 (post-condition$ or post condition$ or postcondition$))	0	L18
L17	L16 and (method$ near9 (post-condition$ or post condition$ or postcondition$))	7	L17
L16	(method$ near5 specification$)	19735	L16
L15	l11 and descendent$	0	L15
L14	L12 and (modif$ Or updat$) and inherit$	1	L14
L13	L12 and overr$	0	L13
L12	L11 and (post condition$ or postconsition$ or post-condition$)	1	L12
L11	6678882.pn.	1	L11

<u>L10</u>	L9 and (post condition$ or postconsition$ or post-condition$)	0	<u>L10</u>
<u>L9</u>	6681383.pn.	1	<u>L9</u>
	DB=TDBD; PLUR=YES; OP=ADJ		
<u>L8</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))and (inherit$ near4 overrid$)	0	<u>L8</u>
	DB=DWPI; PLUR=YES; OP=ADJ		
<u>L7</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))and (inherit$ near4 overrid$)	0	<u>L7</u>
	DB=JPAB; PLUR=YES; OP=ADJ		
<u>L6</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))and (inherit$ near4 overrid$)	0	<u>L6</u>
	DB=EPAB; PLUR=YES; OP=ADJ		
<u>L5</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))and (inherit$ near4 overrid$)	0	<u>L5</u>
	DB=PGPB; PLUR=YES; OP=ADJ		
<u>L4</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))and (inherit$ near4 overrid$)	1	<u>L4</u>
	DB=USPT; PLUR=YES; OP=ADJ		
<u>L3</u>	L2 and (no$ near4 inherit$) near8 overr$	0	<u>L3</u>
<u>L2</u>	L1 and (inherit$ near4 overrid$)	4	<u>L2</u>
<u>L1</u>	(two$ or plural$ Or multiple$) near9 (postcondition$ or post-condition$ or post$ condition$) and (overrid$ near9 (class$ or object$))	5	<u>L1</u>

END OF SEARCH HISTORY

P❂RTAL

US Patent & Trademark Office

Search: ◉ The ACM Digital Library ○ The Guide

class and inherit and post conditions override and descendent

THE ACM DIGITAL LIBRARY

🍀 Feedback Report a problem Satisfaction survey

Terms used
class and **inherit** and **post conditions override** and **descendent** and **specification**   Found **37,566** of **154,226**

Sort results by   [relevance ▼]   🐾 Save results to a Binder   Try an Advanced Search
                                                                             Try this search in The ACM Guide
Display results   [expanded form ▼]   ❓ Search Tips
                                        ☐ Open results in a new window

Results 21 - 40 of 200   Result page: previous 1 **2** 3 4 5 6 7 8 9 10   next
Best 200 shown   Relevance scale ☐ ▬ ▬ ■ ■

21 Modular reasoning in the presence of subclassing
Raymie Stata, John V. Guttag
October 1995 **ACM SIGPLAN Notices , Proceedings of the tenth annual conference on Object-oriented programming systems, languages, and applications**, Volume 30 Issue 10

Full text available: 📄 pdf(1.72 MB)   Additional Information: full citation, abstract, references, citings, index terms

Considerable progress has been made in understanding how to use subtyping in a way that facilitates modular reasoning. However, using subclassing in a way that facilitates modular reasoning is not well understood. Often methods must be overriden as a group because of dependencies on instance variables, and the programmers of subclasses cannot tell which methods are grouped without looking at the code of superclasses. Also, the programmers of subclasses must look at the code of superclasses to te ...

22 Practical predicate dispatch
Todd Millstein
October 2004 **ACM SIGPLAN Notices , Proceedings of the 19th annual ACM SIGPLAN Conference on Object-oriented programming, systems, languages, and applications**, Volume 39 Issue 10

Full text available: 📄 pdf(192.02 KB)   Additional Information: full citation, abstract, references, citings, index terms

<i>Predicate dispatch</i> is an object-oriented (OO) language mechanism for determining the method implementation to be invoked upon a message send. With predicate dispatch, each method implementation includes a predicate guard specifying the conditions under which the method should be invoked, and logical implication of predicates determines the method overriding relation. Predicate dispatch naturally unifies and generalizes several common forms of dynamic dispatch, including traditi ...

Keywords: dynamic dispatch, modular typechecking, predicate dispatch

23 DON: user interface presentation design assistant
Won Chul Kim, James D. Foley
August 1990 **Proceedings of the 3rd annual ACM SIGGRAPH symposium on User interface software and technology**

Full text available: 📄 pdf(1.33 MB)   Additional Information: full citation, references, citings, index terms

Refine Search

Your wildcard search against 10000 terms has yielded the results below.
Your result set for the last L# is incomplete.
The probable cause is use of unlimited truncation. Revise your search strategy to use limited truncation.

Search Results -

Terms	Documents
L2 and (no$ near4 inherit$) near9 overrid$	0

Database:

```
US Pre-Grant Publication Full-Text Database
US Patents Full-Text Database
US OCR Full-Text Database
EPO Abstracts Database
JPO Abstracts Database
Derwent World Patents Index
IBM Technical Disclosure Bulletins
```

Search:

```
L10
```

Refine Search

Recall Text ⬍   Clear   Interrupt

Search History

DATE: Tuesday, May 03, 2005   Printable Copy   Create Case

Set Name side by side	Query	Hit Count	Set Name result set
DB=USPT; PLUR=YES; OP=ADJ			
L10	l2 and (no$ near4 inherit$) near9 overrid$	0	L10
L9	l2 and (no$ near4 inherit$) near9 overrid$	0	L9
L8	l3 and (no$ near4 inherit$) near9 overrid$	0	L8
L7	L6 and (no$ near4 inherit$) near9 overrid$	0	L7
L6	L4 and overrid$ and descend$ and inherit$	35	L6
L5	L4 and overrid$ and descend$ and inherti$	0	L5
L4	L3 and method$ near9 ((post$ near4 condition$) or (postcondition$) or (post-condition$))	39	L4
L3	L2 and (creat$ or generat$) near4 execut$	402	L3
L2	(writ$ Or generat$ or creat$) near4 specification$ and object oriented	867	L2